

MASTS

ELC offers a wide range of masts (5 models in 4 heights), specifically designed for use with "LUMAPHORE®" lighting heads and which all conform to the latest CE standards.

Our masts are designed with:

- Strong sectional tubes and base which are specially designed for greatest overall stability
- Reduced loading height and large locking lever for ease of use
- Locking system and tilt adjustment for optimum safety (EL300-400-ELT300-500)
- Electro-galvanized finish, Epoxy or Teflon paint

The telescopic masts have been designed to give the assembled product maximum rigidity and strength.

ELT 300-500 models reaches height easily due to a worm gear winch drum fitted with polyamide pulleys to reduce cable wear.

All 3, 4 and 5 meters masts are fitted with a telescopic system for use on uneven ground.



Anchor Kit





MASTS - Technical data

Reference - Model	PER0060 - EL200	PER0026 - EL300	PER0016 - EL400	PER0002 - ELT 300	PER0004 - ELT 500
					
Maximum Height	180 cm	310 cm	396 cm	300 cm	510 cm
Description	Standard telescopic mast			Telescopic mast with winch	
Finish	Painted steel	Electro-galvanized steel		Electro-galvanized steel	Covered with Teflon paint
Diameter at ground level	90 cm	154 cm	154 cm	154 cm	174 cm
Loading height	104 cm	152 cm	168 cm	147 cm	165 cm
Weight	5 kg	12,4 Kg	13,6 Kg	16 kg	25 kg
Advantages	Various height position	- safety key - various height positions - adjustable feet - holes for anchor pegs		- winch with cable - adjustable feet - holes for anchor pegs	
Accessories	- Wheel Kit - Mast cover	- Mast Cover - Anchor Kit - Ballast bag		- Wheel Kit	
Compatible with:	- MiniLite - LED 60L - K9-30	- LED 120L - LED 200L - LED 200XL - LED 400L - LED 400XL - CFL 640	- LED 200XL - LED 400XL - CFL 640 fitted with coloured tube	- LED 120L - LED 200L - LED 200XL - LED 400L - LED 400XL - CFL 640	- HI 1000 - HI 2X1000 - LED 400XL - LED 1000XL

Mast wheel



Ballast Kit



Cover mast

