L RANGE

This is our lightest and most compact serie. With a very nice quality/price value, this range gives a sufficient 360° lighting to work safely.



IP44

IK10

230V

2min

360°

Made in FRANCE

Our models



LUMAPHORE® 300L


29 900 Lumens
Illuminated area : 2 400 m²
Power : 200 Watts
IP44 / IK10
Voltage : 230 Volts
Weight : 5.1 Kg



LUMAPHORE® 600L

59 800 Lumens
Illuminated area : 3 200 m²
Power : 400 Watts
IP44 / IK10
Voltage : 230 Volts
Weight : 6.7 Kg

Included accessories



Flight-case

Extremely robust. To transport and protect the LUMAPHORE®.



Suspension ring

To hang up the LUMAPHORE®.

Technical characteristics

		300L	600L
Electric	Total lighting output	200W	400W
	Power supply	230W	450W
	LED's lifetime	50 000 hours	
Security	Protection index	IP44 / IK10	
	Wind resistance	162 Km/h	
	Thermal protection	Yes	
	Operation temperature range	-15°/+40°	
Photometry	Illuminated area	2 400 m²	3 200 m²
	Color temperature	5 000° K	
	Total Lumens	29 900 lm	59 800 lm
	Color rendering index	> 80	
Mechanical	Diameter	22,5 cm	
	Length	62 cm	91 cm
	Weight	5,1 Kg	6,7 Kg
	Sleeve type	Diameter 26 mm	
	Optimum height for use	3 to 4 m	
	Average assembly time	2 minutes	
Standard package	Standard flight-case	Included	
	Power cable (Schuko plug)	7 m	
	Suspension ring	Included	
	Sleeve (diam. 26mm)	Included	
Options & accessories	IP67and IP68 Marechal special plug	In option	
	IP65 switch (ON/OFF)	When ordering	
	4 meters mast	In option	
	Different sleeve (diam., DIN, ...)	When ordering	
	Magnetic holder	In option	