XL RANGE COMPACT MODELS

The XL range's LUMAPHORE® are the most appreciated models thanks to their adaptability to all environments. To increase the ground lighting, they are fitted with 4 additional LED's at the lower part.



Made in FRANCE

IP65

IK10

230V

2min

Our models



LUMAPHORE® 300XL


45 800 Lumens
Illuminated area : 2 400 m²
Power : 300 Watts
IP65 / IK10
Voltage : 230 Volts
Weight : 5.1 Kg



LUMAPHORE® 600XL

76 200 Lumens
Illuminated area : 3 200 m²
Power : 520 Watts
IP65 / IK10
Voltage : 230 Volts
Weight : 7.7 Kg

Included accessories



Flight-case

Extremely robust. To transport and protect the LUMAPHORE®.



Suspension ring

To hang up the LUMAPHORE®.

Technical characteristics

		300XL	600XL
Electric	Total lighting output	300W	520W
	Power supply	355W	575W
	LED's lifetime	50 000 hours	
Security	Protection index	IP65 / IK10	
	Wind resistance	162 Km/h	
	Thermal protection	Yes	
	Operation temperature range	-15°/+40°	
Photometry	Illuminated area	2 400 m²	3 200 m²
	Color temperature	5 000° K	
	Total Lumens	45 800 lm	76 200 lm
	Color rendering index	> 80	
Mechanical	Diameter	22,5 cm	22,5 cm
	Length	62 cm	91 cm
	Weight	5,1 Kg	7,7 Kg
	Sleeve type	Diameter 26 mm	
	Optimum height for use	4 m	
	Average assembly time	2 minutes	
Standard package	Standard flight-case	Included	
	Power cable (Schuko plug)	7 m	
	Suspension ring	Included	
	Sleeve (diam. 26mm)	Included	
Options & accessories	IP67and IP68 Marechal special plug	In option	
	IP65 switch (ON/OFF)	In option	
	IP65 switch (180°/360°)	In option	
	IP65 switch (ON/OFF - 180°/360°)	In option	
	Different sleeve (diam., DIN, ...)	When ordering	
	4 meters mast	In option	
	Magnetic holder	In option	