XLG RANGE

The XLG range's LUMAPHORE® offer an additional functionality: variation of light intensity. Thanks to a control unit, you can increase or decrease the LUMAPHORE® lighting power. In this range, discover the LUMAPHORE® 1500XLG, the most powerful that delivers 220 800 Lumens.



Made in FRANCE

230V

2min

360°

Our models



LUMAPHORE® 600XLG


76 200 Lumens
Illuminated area : 3 200 m²
Power : 520 Watts
IP65 / IK10
Voltage : 230 Volts
Weight : 8.7 Kg



LUMAPHORE® 1500XLG

220 800 Lumens
Illuminated area : 6 000 m²
Power : 1 500 Watts
IP54 / IK08
Voltage : 230 Volts
Weight : 17 Kg

Included accessories



Flight-case

Extremely robust. To transport and protect the LUMAPHORE®.



2 switches box

To turn on / turn off the LUMAPHORE® and to vary its intensity.



Suspension ring

To hang up the LUMAPHORE®.
Included only with 600XLG.

Technical characteristics

		600XLG	1500XLG
Electric	Total lighting output	520W	1 500W
	Power supply	635W	1 770W
	LED's lifetime	50 000 hours	
Security	Protection index	IP65 / IK10	IP54 / IK08
	Wind resistance	162 Km/h	110 Km/h
	Thermal protection	Yes	
	Operation temperature range	-15°/+40°	
Photometry	Illuminated area	3 200 m²	6 000 m²
	Color temperature	5 000° K	
	Total Lumens	76 200 lm	220 800 lm
	Color rendering index	› 80	
	Dimmable	3%-100%	
Mechanical	Diameter	22,5 cm	40 cm
	Length	91 cm	93 cm
	Weight	8,7 Kg	17 Kg
	Sleeve type	Diameter 26 mm	
	Optimum height for use	4 m	5 m
	Average assembly time	2 minutes	3 minutes
Standard package	Standard flight-case	Included	
	Power cable (Schuko plug)	9,4 m	11,4 m
	Suspension ring	Included	When ordering
	IP65 switch (ON/OFF – dimmable)	Included	
	Sleeve (diam. 26mm)	Included	
Options & accessories	IP67and IP68 Marechal special plug	In option	
	Different sleeve (diam., DIN, ...)	When ordering	
	4 meters mast	In option	
	Magnetic holder	In option	-