K45/K65 MOBILE LIGHTING TOWERS

K45 & K65 mobile lighting towers are highly efficient area floodlighting solutions. Made for been used in many environments, headlights can be positioned for 180° to 360° illumination.



IP65

230V

3min

360°

180°

Made in
GREAT-BRITAIN

Technical characteristics

		K45	K65 L3x2	K65 L3x3	K65 L3x4
Electric	Number of headlights	6	3 x 2	3 x 3	3 x 4
	Power supply	650W	730W	1 095W	1 460W
	LED's lifetime	50 000 hours			
	Instant power on	Yes			
Security	Protection index	IP65			
	Wind resistance	72 Km/h	50 Km/h	50 Km/h	50 Km/h
	Operation temperature range	-15°/+40°			
Photometry	Color temperature	6 500 °K	5 000° K	5 000° K	5 000° K
	Total Lumens	83 000 lm	97 000 lm	146 000 lm	195 000 lm
	Dimmable	1% - 100%			
Mechanical	Closed dimensions (L x W x H)	150 x 40 x 40 cm	109 x 83 x 195 cm	109 x 83 x 195 cm	109 x 83 x 195 cm
	Weight	90 Kg	250 Kg	250 Kg	250 Kg
	Optimum height for use	4.5 m	6.5 m	6.5 m	6.5 m
	Average assembly time	3 minutes			

Included accessories



Adjustable, removable wheel kit

For transport by a single person, storage and security.



Independently adjustable legs

Maximum stability when deployed.



Fully adjustable headlights

To suit any lighting application including a 360° light pattern.

